



Catalog No.	Finish	Lamps	Diameter	Height
40714WH	Gloss White	(3) 39W Twin Tube Compact Fluorescent (2G11 base) F39BX by G.E. FT36DL by Osram-Sylvania PL-L 36W by Philips	27"	17" Min. to 46 1/2" Max.
40714PB	Polished Brass Finish			

Features

1. **Canopy:** .032 brass.
2. **Crossbar Assembly**
3. **Fixture Wire:** 18 ga. approx. 60" supplied.
4. **Socket:** (3)
5. **Ballast:** 3 Lt. electronic.
6. **Diffuser:** White translucent acrylic.
7. **Chain:** Steel, approx. 3 feet supplied.
8. **Center Stem:** 1" O.D. steel tubing.
9. **Suspension Rod:** 3/8" O.D. steel tubing.
10. **Ballast Cover/Splice Compartment:** 20 ga. steel, white finish.
11. **Reflector Housing:** 20 ga. steel for white, 14 ga. alum. for polished brass finish.
12. **Holder Knob:** (3) Die-cast aluminum alloy.

Electrical

3 Lt. Rapid Start, High Power Factor, Class "P" electronic ballast. Min. starting temp. 0°F. Input voltage 120V Input watts = 77W.

Mounting

Mounts directly to outlet box using crossbar assembly supplied. Approximately 3 feet of chain and 60 inches of fixture wire are supplied.

Finish

All painted surfaces, baked enamel.

Labels

UL (Suitable for damp locations), I.B.E.W.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes: